

Era Map of Radon Zones

Douglas L. Kladder


National Environmental Health Association Center for Environmental Research and Technology

2004 Children's Environmental Health Regional Summit Salt Lake City, September 7, 2004

Radon Is:

- A significant cause of lung cancer
 - → 1 in 4 lung cancer cases among non-smokers
 - →21,800 lung cancer cases per year in U.S.
- Easy to test for
 - Can be conducted by professionals, maintenance staff and consumers
- All radon concerns can be fixed!
 - Orders of magnitude less than asbestos programs
 - Can benefit other IAQ concerns

Let's get technical, for a moment




What Is Radon?




- Radon is a gas.
- It is naturally occurring.
- It cannot be seen or smelled.
- ☐ It enters buildings from the soil beneath them.

Why Is Radon A Concern?



- Radon further decays into a family of elements called radon decay products
 - Polonium
 - → Lead
 - → Bismuth
- Radon decay products can be inhaled
 - Adhere to lung tissue
 - → Radioactive

Radon Is A Lung Cancer Causing Gas




- Radon decay products inhaled.
- Radon decay products release alpha radiation
- Damaged cell can increase potential for lung cancer.

Alpha Particles Are Strong Enough To Pit Plastic



- Plastic chip from passive radon test (alpha track)
- Magnified only 100 times
- 3 months at EPA
 Action Level of 4
 pCi/L

What Happens When Radon Decay Products Are Inhaled?



Chromosome 6, P53 gene impacted

- Highly radioactive particles stick to lung tissue, where they can irradiate sensitive cells.
- Radiation can alter the cells, increasing the potential for cancer.


EPA & Surgeon General Recommend That People Not Have Exposures Above 4 pCi/L On A Long-Term Basis

- One is advised to take action if a home is at or above 4.0 pCi/L
- Average indoor: 1.3 pCi/L
- Average outdoor: 0.4 pCi/L

How Does Radon Rank As A Cancer Causing Agent?

- Radon is ranked as a Group A carcinogen
 - Highest ranking for cancer potential
 - Known to cause cancer in humans
 - Tobacco smoke and tobacco products in same category
- Provides basis for regulatory and liability concerns!

Are There Just A few Areas Where Radon Concerns Exist?



No!

Many parts of the country have radon concerns.

1 in 15 buildings can be at or above EPA Guidance

Affects:

Schools,

Homes,

Workplaces

The only way to know if levels are elevated is to test!

Short And Long-Term Testing Devices Help Determine the Need for, and Effectiveness of, Radon Mitigation



Short-term test devices




Long-term test devices

Testing Approaches-Schools

- Test during school year and under conditions of occupancy
 - ♦ Not on weekends
- Can be deployed by maintenance staff or professionals
- Every room in contact or above with soil
 - Not upper floors
- Cost:
 - Devices (including analysis): \$15.00/device plus labor


Testing Homes


- Test devices can be deployed by homeowners
 - State agencies
 - CFA
 - Private laboratories
- Cost: \$9.95 to \$15.00 including analysis
 - National Safety Council offers coupons for self-testing
 - Some states have aggressive programs
- Easy



Short-term Radon
Test Device
Easily deployed

All Buildings With Radon Concerns Can Be Fixed!





Active soil depressurization is a means of creating a vacuum beneath a slab or plastic sheet and collecting the radon before it enters a building.

Can't We Just Seal The Cracks?



- Radon can enter through very small openings.
- Without affecting house pressures, sealing is not a stand-alone technique.

Treating Crawl Spaces





- Length of perforated pipe on soil
- High density, 4 mil. cross-linked or 6 mil polyethylene
- Seal to walls, seams and at pads

Perforated Pipe Connected To Suction System



- Perforated pipe connected to solid Sch. 40 PVC pipe
- Riser routed to fan
- Pipe labeled
- Plastic helps dry out crawl space and reduce mildew and odors

System Depressurization Fan



- Installed in attic, garage, or outside
- Must not be installed inside of house
- Quiet
- 90 watt fan runs continuously
- □ 11 year expected life

Suction Point For Slabs And Basements



- Hole cut through slab
- Pit dug out
- PVC pipe connected to hole
- Pipe routed to fan
- May require more than one suction point

System Discharges Away From Building Openings



- Discharge should be high to avoid radon entering building
 - Minimum of 10 feet above grade
 - → 10 feet from openings, 2 feet below discharge
 - Above eave
- Rain cap not recommended
- □ 1/4 inch bird screen

US EPA Mitigation Standards http://www.epa.gov/iaq/radon/pubs/

Mitigation System on School



- Typically external
- Discrete system
- Generally only a small number of rooms must be treated



Mitigation Systems

- Homes
 - → Typically 1 system
 - \diamond Average Cost: \$1,000 or less than $\overline{1\%}$ of value
- Schools
 - → Typically only 5-10% of rooms elevated
 - → Typically 2-3 systems
 - → Cost: <\$15,000 for building</p>
 - Sometimes can be treated by adjusting HVAC system

Pet Peeve - Schools

- Fresh air make-up shut-off
 - Done so to reduce energy cost
 - Reduces dilution
 - Reduces interior pressure
 - → Increases radon levels
 - Causes other IAQ problems



Fresh Air Open



Fresh Air Closed


When to Be Concerned About Radon

- Wherever children are indoors
 - ◆In schools
 - → Daycare
 - At home
- When modifying HVAC systems
- When new buildings are constructed

In other words-in all situations!

EPA Documents


Citizen's Guide





What it is & how to test

Radon in Schools



Testing protocols

Reducing Radon in Schools



How to fix radon

©CERTI

Radon Doesn't Have
To Be A Problem
Unless You Ignore It



Doug Kladder NEHA/CERTI 800-513-8332